

March 29, 2006

INVITATION TO BID

Sealed bids will be received by the City of Auburn, Alabama, until 11:00 a.m., local time, on April 18, 2006, in the Office of the City Manager, 144 Tichenor Avenue, Auburn, Alabama, and then publicly opened and read for furnishing the following:

Self Contained Breathing Apparatus and Face Pieces

Bid specifications are attached. The City is requiring bid prices on approximately 35 Self Contained Breathing Apparatus and Face Pieces. Please direct any questions to Chief Larry Langley at 334.501.3160.

Bids must be submitted on the attached form within a sealed envelope addressed:

City Manager, City of Auburn
144 Tichenor Avenue, Suite 1
Auburn, AL 36830

Envelope must be plainly marked on the outside as follows:

BID: Self Contained Breathing Apparatus and Face Pieces
OPENING: 11:00 a.m., local time
DATE: April 18, 2006

The city reserves the right to select the lowest responsible bidder as the best interest of the city may require, to award the purchase contract from any of the bids, to reject any or all bids, and to waive any informalities in bids received. Bid will be good for ninety (90) days after being opened by the City of Auburn, Alabama.

The successful bidder must possess or obtain appropriate license to conduct business in the City of Auburn, if the nature of the transaction requires such license.

The successful bidder will note that the City pays by invoice on each Friday of the month. Invoices must be received by accounts payable at least seven working days before the scheduled check date. If you have any questions concerning billing, contact our accounts payable office at 334.501.7237.

City of Auburn

Karen S. Broome
Purchasing Officer

General Requirements

One (or more) open circuit, self-contained breathing apparatus consisting of the following major sub-assemblies: 1) full facepiece assembly; 2) an automatic dual path redundant pressure reducing regulator; 3) a removable, facepiece-mounted, positive pressure breathing regulator with air-saver switch, low-pressure alarm and purge valve; 4) a harness and backframe assembly for supporting the equipment on the body of the wearer; 5) a shoulder strap mounted, remote gauge indicating cylinder pressure; 6) an EOS redundant low-pressure alarm.

The unit shall be covered by a warranty providing protection against defects in materials or workmanship. This warranty shall be for a period of eight years on the SCBA, except for the pressure reducer, which shall be covered for 15 years. Electronic components shall be warranted for one year. The SCBA shall be certified by NIOSH/MSHA as conforming to the Code of Federal Regulations, 42 CFR 84. This apparatus, without modification, shall be NIOSH/MSHA certified. The apparatus shall meet all requirements of NFPA-1981 Standard on Open-Circuit, Self-Contained Breathing Apparatus, Current Edition.

Successful bidder agrees to provide, at his own expense, a factory-trained instructor for such time as the department head shall require for complete instruction in the operation and maintenance of the apparatus. Any exceptions to these specifications must be detailed in a separate attachment, and failure to do so will automatically disqualify the bidder. Successful bidder must be a factory-authorized distributor to sell the equipment specified herein.

Facepiece Assembly

The full facepiece assembly shall fit persons of varying facial shapes and sizes with minimal visual interference. It shall be available in three color-coded sizes and maintain NIOSH/MSHA certification of the apparatus regardless of the size used. The lens shall be a single, replaceable, modified cone configuration constructed of a non-shatter type polycarbonate material and be de-signed to meet the impact and penetration requirements of a faceshield as specified in ANSI Z87.1 paragraphs 5.2.8.1 and 5.2.8.2, shall have a silicone based coating to resist abrasion, chemical attack and meet the requirements of NFPA-1981, Current edition for lens abrasion. The lens shall have an anti-fog coating to reduce fogging in stand-by mode.

The face piece shall have a large diameter inlet serving as the female half of a quarter (1/4) turn coupling which mates with the positive pressure breathing regulator. Multi-directional voicemitters shall be lens mounted on both sides of the facepiece lens and ducted directly to an integral silicone nosecup to enhance voice transmission and minimize fogging of the lens. The voicemitters, ducts and nosecup shall be easily removable without the use of tools.

The head harness shall be a four-point suspension made in the fashion of a net hood to minimize interference between securing of the facepiece and the wearing of head protection and be constructed of a Kevlar material. Two flame resistant elastic straps, attached to the lens in four locations, shall provide adjustment for proper face sealing. A four-point attachment rubber head harness shall also be available.

Pressure Reducer

The pressure-reducing regulator shall be mounted on the backframe and be coupled to the cylinder valve through a short length of internally armored high pressure hose with a hand coupling for engagement and sealing within the cylinder valve outlet. In lieu of a manual by-pass, the pressure-reducing regulator shall include a back-up pressure-reducing valve connected in parallel with the primary pressure reducing valve and an automatic transfer valve for redundant control. The back-up pressure reducing valve shall also be the means of activating the low-pressure alarm devices in the facepiece-mounted breathing regulator. This warning shall denote a switch from the primary reducing valve to the back-up reducing valve whether from a mal-function or from low cylinder supply pressure.

A press-to-test valve shall be included to allow bench testing of the back-up reducing valve. The pressure-reducing regulator shall have extended temperature range dynamic O-ring seals composed of fluorosilicone elastomer. The outlet manifold of the pressure reducing regulator shall have incorporated a reseatable over-pressurization relief valve which shall prevent the attached low pressure hose and facepiece-mounted breathing regulator from being subjected to high pressure. An optional outlet manifold shall also have provision for connection of an airline supply for extended duration use while reserving the cylinder supply for egress.

The airline supply hose length shall be up to 300 feet and require an inlet pressure range of 60 to 115 psig, depending on the length of supply hose used. A check valve within the outlet manifold shall prevent the external release of cylinder air in the event the airline supply is either not used or disconnected. Switching from airline supply to cylinder supply shall be accomplished manually by the user, by opening the cylinder valve to prevent inadvertent use of the cylinder supply without the user's knowledge. The outlet manifold shall also contain a second outlet port capable of being fitted with an auxiliary supply hose to support a second breathing regulator for the purpose of rescue only. The auxiliary hose shall be located on the primary wearer's right shoulder and be terminated with a female quick connect fitting which can be easily connected and disconnected by trained individuals with a gloved hand and/or in low light

conditions. The coupling shall also be guarded against inadvertent disconnect during use of the equipment. When operated in this mode, supplying two breathing regulators, the primary wearer's pressure reducer shall be capable of simultaneously supplying each regulator with a flow of at least 200 liters per minute while maintaining positive pressure in the respective facepieces.

Facepiece-Mounted Positive Pressure Regulator

The facepiece-mounted positive pressure-breathing regulator shall supply and maintain air to the facepiece to satisfy the needs of the user at a pressure greater than atmospheric by no more than 1.5 inches of water pressure. The breathing regulator shall maintain this positive pressure during flows of up to 500 standard liters per minute. The regulator shall also meet or exceed a dynamic flow requirement of remaining positive while supplying a minute volume of 160 liters.

The breathing regulator shall have attached a low pressure hose which shall be threaded through the left shoulder strap to couple to the pressure reducing regulator mounted on the backframe. An optional regulator shall be available with a quick connect coupling in line for use with the optional outlet manifold and accessory hose to allow the breathing regulator to be disconnected from the unit and reconnected to the auxiliary hose of a second unit in the event rescue is required. The quick connect coupling shall be easily connected and disconnected by trained individuals with a gloved hand and/or in low light conditions. The coupling shall also be guarded against inadvertent disconnect during use of the equipment. The low-pressure hose shall be equipped with swivel attachments at both ends.

The breathing regulator outlet port shall be configured as the male half of a quarter (1/4) turn coupling which mates with the facepiece and shall be equipped with a doughnut-shaped gasket which provides the seal against the mating surface of the facepiece. The regulator cover shall be fabricated of a flame resistant, high impact plastic. The breathing regulator shall also have an integral low-pressure alarm device that shall combine an audible alarm with simultaneous vibration of the facepiece. This alarm device shall indicate either low cylinder pressure or primary first stage regulator failure. An optional low-pressure alarm shall be integrated into the regulator purge body that provides a visual flashing LED alarm clearly visible to the individual wearing the SCBA. The breathing regulator shall have a demand valve to deliver air to the user, activated by a diaphragm responsive to respiration. The demand valve shall use an extended temperature range dynamic O-ring seal composed of a fluorosilicone elastomer. This diaphragm shall include the system exhalation valve and shall be constructed from a high strength silicone elastomer.

A purge valve shall be situated at the inlet of the breathing regulator and shall be capable of delivering airflow of between 125 and 175 standard liters per minute. The breathing regulator shall be arranged to direct the incoming air over the inner surface of the facepiece for defogging purposes. The components of the breathing regulator shall be constructed of materials that are not vulnerable to corrosion. The flame resistant cover shall contain an air saver switch and pressure demand bias

mechanism. It shall reactivate and supply air only in the positive pressure mode when the wearer effects a face seal and inhales. This device shall not affect the breathing flow through the system while in operation.

End of Service Indicator (EOS)

The SCBA shall have two end-of-service (EOS) indicators. The primary EOS shall be the integral low-pressure alarm device that shall combine an audible alarm with simultaneous vibration of the facepiece. The primary EOS shall be located in the Facepiece-Mounted Positive Pressure Regulator. The secondary EOS shall be the integral high-pressure alarm device that shall be of the type as audible only. The secondary EOS shall be mounted on the user's left side of the SCBA. The high-pressure line to the secondary alarm shall be of stainless steel construction.

Harness and Backframe Assembly

One-Piece Aluminum Version

A lightweight, lumbar support style backframe and harness assembly shall be used to carry the cylinder and valve assembly and the pressure reducing regulator assembly. The backframe shall be a solid, one-piece anodized aluminum frame that is contoured to follow the shape of the user's back. The backframe shall include a mounting for the pressure reducer. This mounting shall contain a slide-type bracket permitting positioning of the pressure reducer to accommodate connection to either an angled or straight-type cylinder valve.

The backframe shall include an over-the-counter, adjustable tri-slide fixture, a Kevlar strap and a double-locking latch assembly to secure 30, 45 or 60 minute cylinders. The harness assembly shall consist of a one size Kevlar strap with a stripe. This harness shall include box-stitched construction with no screws or bolts. The harness assembly shall incorporate parachute-type, quick-release buckles and shall include shoulder and hip pads. The harness shall include a seat-belt type waist attachment. The backframe shall include accommodation and mounting spaces suitable for installation of a distress alarm integrated with the SCBA. These mounting spaces shall permit installation of an alarm sensor module in an area between the cylinder hanger locking mechanism and the backframe.

Distress Alarm Integrated with SCBA

General Specifications

The distress alarm shall be capable of integration with a NIOSH certified self-contained breathing apparatus, and this integrated SCBA and distress alarm system shall retain NIOSH certification. . The system shall meet all requirements of NFPA-1982 Standard on Personal Alert Safety Systems (PASS), 1998 Edition
Operation of this distress alarm shall be initiated with the opening of the valve of an SCBA cylinder charged to a minimum pressure of 30 to 80 psig. A visual indication of automatic mode activation shall consist of a green flashing LED on the system's control module.

Dual Alarms

The system shall incorporate dual visual and audible alarms, which shall be activated in a pre-alarm mode when the system remains CITY OF AUBURN motionless for approximately 20 seconds. A full alarm shall be activated in the event the system remains motionless for approximately 30 seconds. Visual signals shall consist of a green flashing LED when the system is in operation and red flashing LEDs to indicate pre-alarm mode, full alarm mode and a low battery condition. The system's LED signals shall be situated on a control console assembly mounted on the user's right shoulder strap. The system shall have a visual LED indicator to check the battery condition while the system is not in use.

The Alarm signal shall be in a frequency range of 1 kHz to 4 kHz and consist of three primary frequencies. Sound pressure level shall be >95 dBA. The Pre-alarm signal shall be in a frequency range of 1 kHz to 2 kHz and consist of two primary frequencies, the sound pressure level shall ramp up in two distinct steps from 60 to >100 dBA.

Control Module

The pressure gauge shall become an integral part of the control module assembly. The control module assembly shall contain push buttons for manual operation of the distress alarm. A yellow color-coded push button shall permit system re-set; a red color-coded push button shall permit manual activation of the full alarm mode. Both push buttons shall be recessed to minimize accidental activation. The system shall feature a "hands-free" re-set capability that may be activated by means of a slight movement of the SCBA when the system is in a pre-alert mode.

Cables connecting the control console assembly and sensor module assembly shall be capable of withstanding approximately 150 pounds of tension.

Sensor Module

The system shall include a sensor module mounted to the SCBA backframe and located in an area between the cylinder and backframe in a manner designed to protect the assembly from damage. The system shall be powered by a 9-volt alkaline battery. A second 9-volt alkaline battery shall be reserved solely to power the system's independent audible and visual alarm circuit. The batteries shall be housed in a battery compartment separated from sensor and control circuits and sealed with a gasketed cover. The sensor module shall contain dual sound emitters for the audible alarm.

Intrinsically Safe

The distress alarm system shall be ETL listed as intrinsically safe in accordance with ANSI/UL913 for use in Class 1, Division I, Groups A, B, C and D Hazardous locations. The system shall weigh approximately 1.9 pounds.

CITY OF AUBURN

BID PROPOSAL

**Approximately Thirty-Five (35) Self Contained Breathing Apparatus and
Approximately Ninety-Five (95) Face Pieces**

TO: City of Auburn

We, the undersigned, propose to furnish the items listed below and guarantee that if we are awarded the bid, we will furnish these goods in accordance with the attached specifications.

YOU MUST SPECIFY THE EXACT EQUIPMENT BEING BID
(Enclose brochures/description documents if needed)

PRICE WILL BE GUARANTEED FOR ONE YEAR

PRICE:

Self Contained Breathing Apparatus Frame _____

Self Contained Breathing Apparatus Face Pieces _____

ESTIMATED DELIVERY DATE: _____

DELIVERY DATE IS IMPORTANT CONSIDERATION

Exceptions: _____

Authorized Signature

Name of Company

Printed Name

Address

Date

City, State Zip

Phone/Fax Number